

Certification
Issued Under the Authority of the
Federal Communications Commission

By:

Bay Area Compliance Laboratory Corp.
1274 Anvilwood Avenue
Sunnyvale, CA 94089

Date of Grant: 08/20/2018

Application Dated: 08/20/2018

Pycom Ltd
High Point 9 Sydenham Road
Guildford Surrey GU1 3RX
Surrey,
United Kingdom

Attention: Daniel Campora

NOT TRANSFERABLE

EQUIPMENT AUTHORIZATION is hereby issued to the named GRANTEE, and is VALID ONLY for the equipment identified hereon for use under the Commission's Rules and Regulations listed below.

FCC IDENTIFIER: 2AJMTFIPY01R
Name of Grantee: Pycom Ltd
Equipment Class: Licensed Non-Broadcast Station Transmitter
Notes: FiPy Module
Modular Type: Single Modular

| <u>Grant Notes</u> | <u>FCC Rule Parts</u> | <u>Frequency Range (MHZ)</u> | <u>Output Watts</u> | <u>Frequency Tolerance</u> | <u>Emission Designator</u> |
|--------------------|-----------------------|------------------------------|---------------------|----------------------------|----------------------------|
| | 27 | 1710.0 - 1755.0 | 0.188 | 2.5 PM | 1M14G7D |
| | 27 | 1710.0 - 1755.0 | 0.194 | 2.5 PM | 1M01D7W |
| | 27 | 699.0 - 716.0 | 0.211 | 2.5 PM | 1M12G7D |
| | 27 | 699.0 - 716.0 | 0.174 | 2.5 PM | 990KD7W |
| | 27 | 777.0 - 787.0 | 0.178 | 2.5 PM | 1M14G7D |
| | 27 | 777.0 - 787.0 | 0.185 | 2.5 PM | 986KD7W |

Modular Approval. Output power listed is conducted at antenna terminal. This device supports 1.4 MHz bandwidth mode (CAT-M1) with LTE Band 4/12/13. This module is approved for use only in the mobile configurations associated with this filing. This grant is valid only when the module is sold to OEM integrators and must be installed by the OEM or OEM integrators. Compliance of this device in all final host configurations is the responsibility of the Grantee. The antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not transmit simultaneously with any other antenna or transmitter, except as evaluated in this filing or in accordance with FCC multi-transmitter product procedures. Antenna gain including cable loss must not exceed 7.0 dBi in the Band 4, 9.81 dBi in Band 12, and 10.75 dBi in Band 13 for the purpose of satisfying the requirements of CFR 47 2.1043 and 2.1091. OEM integrators and end-Users must be provided with transmitter operation conditions for satisfying RF exposure compliance. This device contains functions that are not operational in U.S. Territories. This filing is only applicable for U.S. operations.